

Floor Scrubber-Dryers

Reliable floor scrubbers-dryers that offer a simple, straight-forward ownership experience at the right price.

416S

35CM MICRO WALK-BEHIND SCRUBBER-DRYER



Maneuverable to scrub in difficult to reach spaces



Simple and comfortable to operate



Large tank capacity in small size machine



1040S

50CM WALK-BEHIND SCRUBBER-DRYER



Maneuverable, with easy-to-use pad assist or self-propel operation



Solution control with automatic stop



Robust construction in a compact scrubber-dryer



Self-leveling brush for maximum cleaning performance



1870S

60/70CM WALK-BEHIND SCRUBBER-DRYER



Easy to maneuver with forward and reverse self-propel



Solution control with automatic stop



Durable construction in a mid-size scrubber-dryer



Self-leveling brush with high RPM for maximum cleaning efficiency



2180SR

50/60CM MICRO-RIDER FLOOR SCRUBBER-DRYER



Quickly reach many areas of a facility with a ride-on scrubber-dryer



Compact design easily fits into most congested areas



Simple to operate control panel with visual display



Quiet operation allows for cleaning anytime



SPECIFICATIONS



	416S	1040S		1870S		2180SR	
Scrubbing width	350 mm	500 mm		600 mm	700 mm	500 mm	600 mm
Battery voltage	24V (2 x 12)	24 V (2x12)		24 V (2 x 12)		24 V (2 x 12)	24 V (4 x 6)
Battery type	29 Ah - AGM	105 Ah - GEL		105 Ah - GEL		105 Ah - GEL	180 Ah - GEL
Max up-to running time (mins)	90	132		78		150	210
Brush speed	140 rpm	155 rpm		215 rpm		150 rpm	220 rpm
Maximum down pressure	25 kg	18 kg		30,5 kg	31,5 kg	22 kg	50 kg
Scrub head raise/lower	n/a	Manual with foot pedal		Manual with foot pedal		Actuator	
Brush motor	200 W	550 W		2 x 300 W		400 W	
Theoretical productivity	1.300 m ² /hr	2.250 m ² /hr	1.750 m ² /hr	2.579 m ² /hr	2.848 m ² /hr	3.180 m ² /hr	3.684 m ² /hr
Solution tank capacity	16 L	40 L		70 L		78,5 L	
Recovery tank capacity	19 L	50 L		75 L		80 L	
Vacuum motor power	3 stage, 550 W	480 W		480 W		2 stage, 480 W	3 stage, 480 W
Squeegee width	450 mm	815 mm		815 mm	1.010 mm	710 mm	942 mm
Squeegee raise/lower	Hand lever	Hand lever		Hand lever		Actuator	
Squeegee blade replacement	No-tool	No-tool		No-tool		No-tool	
Propel	Pad assist	Self-propel	Pad assist	Self-propel		Self-propel, foot pedal	
Maximum speed	3,5 km/h	4,5 km/h	3,5 km/h	4,2 km/h		6 km/h	
Maximum climbing angle	n/a	2%	-	2%		8%	16%
Turning radius (wall to wall)	n/a	-		-		1.851 mm	1.853 mm
Dimensions (LxWxH)	950 x 450 x 1200 mm	1.230 x 516 x 960 mm		1.210 x 680 x 960 mm	1.220 x 748 x 960 mm	1.310 x 673 x 1.030 mm	
Weight (w/out battery)	36 kg	73 kg	67 kg	93,7 kg	94,5 kg	118 kg	134 kg

WARRANTY

12 months on parts and labour, excluding wear items, see your local representative for more information.