T681

Small ride-on scrubber-dryer

Big productivity in a small rider
Small size design, intuitive controls with large display delivers versatile operation to provide excellent performance and efficient cleaning. The T681 is ideal for cleaning large spaces in areas such as retail stores, hospitals and schools.

Worry-free operation and maintenance with optional lithium ion batteries.

Maneuverable and productive
Reach many areas of the facility and get more cleaning done with compact design and maximize productivity with a wide scrub head and large solution tank capacity.

Simple operation
Ease of start up and quick training using one button cleaning operation with adjustable cleaning settings on large, intuitive control panel.

Chem-Dose system
Increase consistent cleaning performance and reduce cost to clean with integrated chemical dosing system, standard.

Inside the **T681**

1. **Easily change multiple** cleaning functions from intuitive control panel.
2. **High-performance 3-stage vacuum motor** for recovering more water.
3. **Reach more areas** of the facility with excellent ramp climbing capability from a strong front traction motor.
4. **Reduce maintenance time** by easily accessing service areas with removable panels.
5. **Consistent water pick-up** with durable "V" shaped squeegee design and standard Linatex® squeegee blades.
6. **Simple no-tools** brush change system.

T681 specifications

FEATURE	DISK	DISK	CYLINDRICAL
Cleaning path	700 mm	850 mm	700 mm
Productivity (per hour) theoretical max	4192 m^2/hr	5073 m^2/hr	4192 m^2/hr
Estimated coverage (per hour)*	2574 m^2/hr	3157 m^2/hr	2574 m^2/hr
Scrubbing speed		6,0 kmh	
Scrub head and squeegee raise/lower		independent actuators	
Brush/pad speed	200 rpm		880 rpm
Brush/pad pressure	From 10 to 50 kg		From 6 to 23,5 kg
Solution tank capacity		100 L	
Recovery tank capacity		110 L	
Battery run time - up-to hours**		3,5	
Battery voltage	24V (4 x 6V)	24V (4 x 6V)	24V (4 x 6V)
Dimensions (LxWxH)	1504 x 759 x 1200 mm	1504 x 909 x 1200 mm	1504 x 830 x1200 mm
Squeegee width	940 mm	1089 mm	1089 mm
Weight (with heaviest battery)	336 kg	353 kg	339 kg
External radius (wall to wall)		1960 mm	
Maximum climbing angle		16%	
Sound level (operator's ear)***		75 dB	
Chem-Dose tank capacity		5 L	

Specifications subject to change without notice.
** Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.*
*** Run times are based on Continuous Scrubbing Run Times.*
**** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA*

T681 lithium ion specifications

FEATURE	SELF PROPEL DISK			
Cleaning path	700 mm		850 mm	
Productivity (per hour) theoretical max	4192 m^2/hr		5073 m^2/hr	
Estimated coverage (per hour)*	2574 m^2/hr		3157 m^2/hr	
Scrubbing speed	6,0 kmh			
Scrub head and squeegee raise/lower	independent actuators			
Brush/pad speed	200 rpm			
Brush/pad pressure	From 10 to 50 kg			
Solution tank capacity	100 L			
Recovery tank capacity	110 L			
Battery Type	50 Ah Lithium-Ion	90 Ah Lithium-Ion	50 Ah Lithium-Ion	90 Ah Lithium-Ion
Charger Type	Off board charger			
Battery charging time up-to hours**	2h			
Battery run time - up-to hours**	2h	3h	2h	3h
Battery voltage	27,8			
Dimensions - L x W x H	1504 x 759 x 1200 mm		1504 x 909 x 1200 mm	
Squeegee width	940 mm		1089 mm	
Weight (with heaviest battery)	414		431	
External radius (wall to wall)	1960 mm			
Maximum climbing angle	16%			
Sound level (operator's ear)***	75 dB			
Chemical dosing	Option available			
Chem-Dose tank capacity	5L			

Specifications subject to change without notice.
** Estimated coverage rates use the practical speed and empty/fill time standards from the 2004 ISSA Cleaning Times handbook.*
*** Run times are based on Continuous Scrubbing Run Times.*
**** Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA*

For a demonstration or additional information,
call **+32 3 217 94 11** or email **europe@tennantco.com**

©2025 The Tennant Company logo and other trademarks designated with the symbol "®" are trademarks of Tennant Company registered in the United States and/or other countries. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

Tennant Europe
tennant.eu